





# 24" Convertible Open Frame Touch Monitor

#### **Effortless Multi-Touch Experience**

Projected Capacitive touch technology provides a smooth, effortless multi-touch experience—identical to many of your favorite mobile touch devices.

#### **Greater Durability**

Optically bonded cover glass provides a highly durable surface for longer, trouble-free service life.

#### Sophisticated Bezel-Free Design

Smooth multi-touch surface across the entire face of the monitor for refined aesthetics and easy cleanability.

## Display Details

K24D-0311
23.8" TFT - Active Matrix
527.0 H x 296.5 V mm
WLED
16:9
1920x 1080
16.7 M
0.297 H x 0.297 V mm
225 cd/m <sup>2</sup>
3000:1
178°
178°
16 ms

### Touch Details

Touch Technology	Projected Capacitive
Multi-Touch Input	10 points
Input Method	Finger, Thin Glove
Touch Interface	USB-Type B
Multi-Touch OS Support	Windows , Linux , & Android

## Dimensions and Weight

Display (WxHxD)	569.2 x 341.1 x 42.4 mm
Display Weight	Kg
Shipping Weight	Kg
Shipping Weight	Kg

## **Product Details**

Power Supply	12V DC Lockable Connector, 4.16A
Power Consumption	Operating: 25 W Sleep: 2 W Off: 0.5 W
Video Input	Analog VGA, DP, HDMI
Audio Input	None
<b>Mounting Options</b>	VESA Mount, Flush Mount w/ bracket
VESA Pattern	100 x 100 mm
Operating Conditions	0°C to +50°C, Noncondensing 80%
Storage Conditions	-20°C to +60°C, Noncondensing 90%
Agency Approvals	CE, FCC-B, RoHS
Warranty	3 year

The information presented in this specification sheet is intended as general information about TPK America, LLC products and is subject to change.

Product specifications and warranties will be governed by TPK America, LLC standard terms and conditions of sale. Products are subject to availability. 100417R1

