

UCA

UCA SERIES



UCA 1 UCA 3
UCA 2 UCA E

FEATURES

- Wide working temperature for coin acceptance.
- Coin sorter option available for UCA1 UCA2.
- Eight coin channels available at once.
- Mechanical and Electrical anti-string function.
- Acceptance speed up to 3 coins per second.

SPECIFICATIONS

Acceptance Rate

96% or greater.

*Note: The incomplete bills such as extremely dirty, wet, broken or wrinkle ones are excluded.

Interface

Pulse, RS232 (TTL level)

Accepting Speed

2~3 coins/sec

Coin Accepted Size

Diameter : 16mm~33mm
Thickness: 1.6mm~3.3mm

Dimension

147.5 x 72.4 x 124 mm
(5.8 x 2.85 x 4.88 inches)

Power Source

12 V DC (10V~16V DC)

Power Consumption

Standby : 0.05A, 0.6W
Operation: 0.2 A, 2.4W
Maximum: 0.5 A, 6 W

Weight

Approx. 0.35 kg

Operation Environment

Operation Temperature: -5°C~60°C
Storage Temperature: -20°C~75°C
Humidity: 30%~85% RH
(no condensation)

Installation

Indoor

Application

Amusement, Vending, Kiosk